

Transportable Wide Band Antenna

The TWB is a transportable broadband HF antenna system that can enhance your communication experience, perfect for seamless communication in any scenario.

This fully integral system comes with its own fiberglass sectional mast, eliminating the need for natural support objects during setup.

Packed in a convenient roll-up kit bag, the complete HF antenna system and mast are easily transportable. You can have it erected and "on air" in as little as 15 minutes, ensuring swift and efficient deployment.



Antennas	TWB2530/100	TWB2530/400	TWB2530/1K
Frequency range	2.5 to 30MHz	2.5 to 30MHz	2.5 to 30MHz
Bandwidth	Broadband	Broadband	Broadband
Power rating	100W	400W	1000W
SWR	Better than 2.5:1	Better than 2.5:1	Better than 2.5:1
Impedance	50 Ohm	50 Ohm	50 Ohm
Polarisation	Horizontal	Horizontal	Horizontal
Antenna Elements	PVC coated braided copper with Kevlar core	PVC coated braided copper Kevlar	PVC coated braided copper Kevlar
Antenna configuration	Inverted V	Inverted V	Inverted V
Footprint	48m x 2.5m (22m mast stays)	48m x 2.5m (22m mast stays)	48m x 2.5m (22m mast stays)
Mast requirements	Single 11m	Single 11m	Single 11m
Input connector	N Type	N Type	N Type
Packed Dimensions	2.1m x 0.35m x 0.3m	2.1m x 0.35m x 0.3m	2.1m x 0.35m x 0.3m
Cable	20m x UR67 N Type	20m x UR67 N Type	20m x UR67 N Type